



Technische Daten Technical data	AC 500 Solid* ³	AC 2000 Solid* ²	AC 3000 Solid* ^{1,2}
Normgebläseleistung (m ³ /h) Standard blower capacity (m ³ /h)	1700	4400	2500
Absaugleistung effektiv bis ... (m ³ /h) Sucking capacity effective, till ... (m ³ /h)	700	2500	1200
Druckdifferenz (Pa) Standard pressure (Pa)	900	2100	900
Geräuschpegeln (dB (A)) Noise level (dB (A))	< 70	< 75	< 75
Filterfläche (m ²) Filter surface (m ²)	8,0	18,0	12,4
Motorleistung (kW) Motor output (kW)	0,5	2,2	0,68
Abmessungen (L x B x H mm) Dimensions (L x W x H mm)	500 x 500 x 590	700 x 700 x 2110	740 x 623 x 613
Gewicht ca. (kg) Weight approx. (kg)	50	260	100
Elektrischer Anschluss (V, Hz, A) Electrical power connection (V, Hz, A)	230, 50, 2,40	3 x 400, 50, 4,55	230, 50, 3,10

*1 über Stufenschalter einstellbar

*2 auch lieferbar mit 60 Hz Netzfrequenz

*1 adjustable by step switch

*2 available also with 60 Hz cycles